In the following pages are listed the cups for which each support is suited.
They are specially shaped to perfectly adhere to the internal profile of the cups and they are provided with a male or female axial pin in order to allow suction, as well as to fasten them to the machine. These cups can be manually assembled onto them with a simple pressure, with no adhesives. They are made with nickel-plated brass or anodised aluminium or with special materials upon request.

Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 01	2.90	3	5	10	18	brass	01 04 10	4.0
							01 05 10	
							01 06 10	
00 08 02	4.75	3	5	10	18	brass	01 08 10	4.0
							01 09 07	



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 03	5.5	5	8	7	20	brass	01 10 10	9.0
							01 11 16	
							01 12 10	
							01 14 10	
							01 14 32	
							01 15 10	
							01 16 20	
							01 17 12	
							01 18 10	
							01 20 10	
							01 20 24	
							01 22 10	
							01 25 28	



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 04	5.5	13	9	7	20	brass	01 10 10	8.1
							01 11 16	
							01 12 10	
							01 14 10	
							01 14 32	
							01 15 10	
							01 16 20	
							01 17 12	
							01 18 10	
							01 20 10	
							01 20 24	
							01 22 10	
							01 25 28	



Convertion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS-NPT thread adapters available at page 1.117



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 05	7.5	5	8	9.5	22.5	brass	01 15 15 01 25 15 01 30 15 01 40 80 01 42 90	10.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 06	5.25	4.5	4	8.5	17	AVP	01 06 50 01 08 50 01 11 50 01 11 16 01 16 20 01 17 12	2.6



Art.	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 07	10	5	9.5	14.5	brass	01 18 50 01 20 60	4.8



Art.	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 08	12	4.5	10	14.5	brass	01 19 17 01 25 10 01 30 10 01 35 10	2.7



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 09	16	8	14	15	37	aluminium	01 19 31 01 40 70 01 75 31	18.1

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 10	10.5	8	14	14	36	brass	01 22 24 01 22 45 01 22 99	30.3



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 14	7.5	13	9	9.5	22.5	brass	01 25 15 01 30 15 01 40 80 01 42 90	9.8



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 15	12	8	14	15	37	aluminium	01 25 35 01 27 24 01 30 24	12.3



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 18	9.5	8	14	10	32	aluminium	01 16 26 01 30 50 01 30 55 01 30 99 01 40 50	10.3





Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 19	9	5	12	18	35	brass	01 32 36	22.7



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 20	12	8	14	10	32	aluminium	01 35 15 01 40 15 01 45 15	11.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 21	12	17	13	10	27	aluminium	01 35 15 01 40 15 01 45 15	9.3



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 22	25	10	14	7.5	25	aluminium	01 45 10 01 60 10	5.9

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 24	12	8	14	12	34	aluminium	01 50 20 01 65 28	10.3



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 26	14.5	8	14	13.5	35.5	aluminium	01 52 50	13.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 28	25	12	14	8	37.3	aluminium	01 85 10	13.4



Art.	A Ø	B	D	F	H	Support material	Cup art.	Weight g
00 08 29	15.5	M12	25	18	23.5	aluminium	01 85 10	6.6



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	N	O	P	Q	Support material	Cup art.	Weight g
00 08 31	60	25	55	20	aluminium	01 40 75	34.1



Art.	A Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 32	60	64	3	10	aluminium	01 64 15 01 65 15 01 85 15	80.6



Art.	A Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 33	88	92	3	11	aluminium	01 92 15 01 110 10	188.9

Convertion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$



Art.	N	O	P	Q	Support material	Cup art.	Weight g
00 08 34	107	75	102	70	aluminium	01 107 75 01 120 90	215.5



Art.	A Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 35	120	127	4	15	aluminium	01 150 10	471.3



Art.	D Ø	F	G	H	Support material	Cup art.	Weight g
00 08 44	25	14	7.5	25	aluminium	01 45 10 01 60 10	5.1



Art.	A Ø	B Ø	D Ø	F	H	Support material	Cup art.	Weight g
00 08 46	15.5	G1/4"	25	18	23.5	aluminium	01 85 10	6.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 50	9.5	17	13	10	27	aluminium	01 16 26 01 30 50 01 30 55 01 30 99 01 40 50	8.5



Art.	A Ø	C Ø	D Ø	F	H	M	Support material	Cup art.	Weight g
00 08 58	160	G3/8"	180	5	12	60	aluminium	01 180 15	740.0



Art.	N	O	P	Q	Support material	Cup art.	Weight g
00 08 59	135	60	130	55	aluminium	01 135 60 01 150 75	218.4

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 60	12	6.5	8	14.5	brass	01 19 17 01 20 08 01 20 60 01 25 08 01 25 10 01 26 10 01 30 10 01 35 10	5.6



Art.	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 61	10	4.5	10	14.5	brass 01 20 60	01 18 50	6.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 62	10	13	9	3	16	brass	01 18 50 01 20 60	9.4



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 64	6.5	13	10	7.5	20.5	brass	01 14 15 01 15 23 01 18 12 01 18 23 01 18 29 01 18 35	13.9



Art.	D Ø	E	F Ø	G	H	Support material	Cup art.	Weight g
00 08 65	6.5	13	M5	7.5	20.5	brass	01 14 15 01 15 23 01 18 12 01 18 23 01 18 29 01 18 35	13.7



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	D Ø	E	F Ø	G	H	Support material	Cup art.	Weight g
00 08 66	6.5	13	M5	7.5	20.5	brass	01 14 15 01 15 23 01 18 12 01 18 23 01 18 29 01 18 35	13.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 67	6.5	5	8	7.5	20.5	brass	01 14 15 01 15 23 01 18 12 01 18 23 01 18 29 01 18 35	11.4



Art.	A Ø	B Ø	C Ø	D Ø	E	F	G	H	N Ø	Support material	Cup art.	Weight g
00 08 68	40	M12	23	35	7	10	18	25	20	aluminium	01 46 13	47.2
00 08 72	65	G3/8"	40	60	10	15	25	35	25	aluminium	01 73 14	169.1
00 08 73	76	G3/8"	51	71	10	15	27	37	25	aluminium	01 95 14	266.0



Art.	B Ø	E	F	Support material	Cup art.	Weight g
00 08 70	G1/8"	8.5	6.5	aluminium	01 12 20	5.4



Fixing plate art. 00 08 97

TSP perforated screw M3x5 art. 00 08 103

Note: By ordering art. 00 08 70 you will also receive the fixing plate and the TSP perforated screw

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	A	B Ø	C	E	F	Support material	Cup art.	Weight g
00 08 71	30	G1/8"	25	8.5	6.5	aluminium	01 12 30	7.8
00 08 75	40	G1/8"	35	8.5	6.5	aluminium	01 12 40	11.4
00 08 76	55	G1/8"	50	8.5	6.5	aluminium	01 12 50	15.5



Fixing plate art. **00 08 98** for supp. **00 08 71**
art. **00 08 99** for supp. **00 08 75**
art. **00 08 100** for supp. **00 08 76**



2 TSP screws M3x5 art. **00 08 102**



Note: By ordering the article associated with the support, the fixing plate and the TSP screws will also be provided.



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 81	22	8.5	14	3.5	22.5	aluminium	01 40 18 01 48 18 01 54 18	8.8



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 82	8.5	5	8	9.5	22.5	brass	01 25 12 01 33 50	11.2



Art.	F	G	H	Support material	Cup art.	Weight g
00 08 83	11	7.5	14.5	aluminium	01 56 15	67.4



VACUUM CUP SUPPORTS



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 101	9	5	8	8	21	brass	01 25 14	10.8



Art.	A Ø	B Ø	C Ø	D Ø	F	H	M	Support material	Cup art.	Weight g
00 08 107	120	M12	G3/8"	127	4	15	30	aluminium	01 127 15 01 150 10	476.9



RING NUT

Art.	A Ø	B Ø	C Ø	D Ø	H	Ring nut material	Support art.	Weight g
00 08 109	G1/4"	2.5	25.5	34	4.5	aluminium	00 08 108	9.8
00 08 111	G3/8"	2.5	25.5	34	4.5	aluminium	00 08 110	8.7
00 08 113	G3/8"	4.0	45.0	69	6.0	aluminium	00 08 112	58.2



SUPPORT

Art.	A Ø	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 108	G1/4"	35	9	19.5	4.5	33.0	aluminium	01 76 24 01 90 24 01 110 24	21.4
00 08 110	G3/8"	35	9	19.5	4.5	33.0	aluminium	01 76 24 01 90 24 01 110 24	25.0
00 08 112	G3/8"	69	15	22.0	5.5	42.5	aluminium	01 150 36	73.9

Note: By ordering the support, you will automatically receive its associated ring nut.

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	A Ø	B Ø	C Ø	D Ø	E	H	M	Support material	Cup art.	Weight Kg
00 08 115	223	M12	G3/8"	230	5	15	70	aluminium	01 250 20	1.65



Art.	A	B	D Ø	E	H	M	N	Support material	Cup art.	Weight Kg
00 08 116	290	68	G3/8"	3	11	284	62	aluminium	01 290 68 01 300 80	0.53



Art.	A	B	D Ø	E	H	M	N	Support material	Cup art.	Weight Kg
00 08 117	290	140	G1/2"	3	11	284	134	aluminium	01 290 140 01 300 150	1.13



Art.	B Ø	D Ø	H	Support material	Cup art.	Weight g
00 08 118	G1/4"	40	10	aluminium	01 42 15	32.1



Art.	A Ø	B Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 119	120	G3/8"	127	4	15	aluminium	01 150 10	478.9



Art.	A Ø	B Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 123	88	G3/8"	92	3	11	aluminium	01 110 10 01 92 15	186.1



Art.	A Ø	B Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 126	45	M12	54	3	10	aluminium	01 75 42 01 80 20	45.5

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 127	13.5	8	14	15	37	aluminium	01 40 25 01 56 30 01 75 30	24.7



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 132	8.5	12	8	5	17	aluminium	01 20 23 01 22 19 01 34 26	3.8



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 133	8.5	5.5	8	5	18.5	aluminium	01 20 23 01 22 19 01 34 26	3.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 134	10	14	10	7.5	21.5	aluminium	01 30 32 01 40 42 01 43 28	8.3



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	E	F	G	H	Support material	Cup art.	Weight g
00 08 135	7.5	12	7.5	27	aluminium	01 30 32 01 40 42 01 43 28	9.5



Art.	E	F	G	H	Support material	Cup art.	Weight g
00 08 136	12	14	8	37.3	aluminium	01 85 10	9.2



Art.	E	F	G	H	Support material	Cup art.	Weight g
00 08 141	14	10	9.5	23.5	aluminium	01 50 53 01 53 35	19.7



Art.	E	F	G	H	Support material	Cup art.	Weight g
00 08 142	7.5	12	9.5	29	aluminium	01 50 53 01 53 35	15.7

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	A Ø	B Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 143	45	G1/2"	54	3	10	aluminium	01 75 42 01 80 20	41.5



Art.	N	O	P	Q	Support material	Cup art.	Weight g
00 08 144	135	50	130	45	aluminium	01 135 50 01 150 65	176.1



Art.	A Ø	B Ø	C Ø	D Ø	E	H	M	Support material	Cup art.	Weight g
00 08 145	120	G3/8"	G3/8"	127	4	15	27	aluminium	01 150 10	471.9

Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 146	8	5	8	5	18	brass	01 20 12 01 20 14 01 20 15	9.8



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	B Ø	D Ø	H	Support supporto	Cup art.	Weight g
00 08 147	M12	40	10	aluminium	01 42 15	32.8



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 148	12	7.5	12	15	34.5	aluminium	01 50 70	14.5



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 155	8	13	9	5	18	brass	01 20 12 01 20 14 01 20 15	9.1



Art.	A Ø	C Ø	D Ø	E	N	H	Support material	Cup art.	Weight g
00 08 162	61	G1/8"	70	3	23	10	aluminium	01 110 58	78.9

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6}$ = $\frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



Art.	A Ø	B Ø	C Ø	D Ø	E	N	H	Support material	Cup art.	Weight g
00 08 163	98	G1/2"	G1/8"	107	3	35	10	aluminium	01 150 74	211.8



Art.	C Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 172	M8	8	14	15	37	aluminium	01 40 25 01 56 30 01 75 30	15.2



Art.	N	O	P	Q	Support material	Cup art.	Weight g
00 08 184	60	25	55	20	aluminium	01 40 75	38.7



Art.	A Ø	B Ø	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 231	15	G1/8"	36	10	4	14	aluminium	01 31 06	24.9



Art.	A Ø	B Ø	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 232	15	G1/8"	30	10	4	14	aluminium	01 24 06	16.7



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 236	8	5	5	5	15	brass	01 07 13	3.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 237	6	5	5	4	14	brass	01 08 07	3.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 238	5.7	7	7	6	20	brass	01 11 08	7.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 239	4	5	8	6.5	19.5	brass	01 14 09	8.0



Art.	D Ø	E	F	G	H	Support material	Cup art.	Weight g
00 08 240	4	13	9	6.5	19.5	brass	01 14 09	7.0

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

Art.	D Ø	F	H	Support material	Cup Art.	Weight g
00 08 241	8	9	10	brass	01 15 04	1.5



Art.	D Ø	F	H	Support material	Cup Art.	Weight g
00 08 242	11	9	9.5	brass	01 20 04	1.8



Art.	D Ø	F	H	Support material	Cup Art.	Weight g
00 08 243	15	10	13	brass	01 20 06	6.0



Art.	D Ø	E	F	H	Support material	Cup Art.	Weight g
00 08 244	14	6.5	8	14.5	brass	01 35 12	5.9



Art.	D Ø	E	F	G	H	Support material	Cup Art.	Weight g
00 08 245	6.5	4.5	6	8	18.5	brass	01 20 11	2.7



Art.	D Ø	F	H	Support material	Cup Art.	Weight g
00 08 246	14	8	10	brass	01 22 06	5.0



Art.	D Ø	F	H	Support material	Cup Art.	Weight g
00 08 247	14	8	17	brass	01 40 14	8.4



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

VACUUM CUP SUPPORTS



Art.	D Ø	F	H	Support material	Cup art.	Weight g
00 08 248	24	14	23.5	aluminium	01 54 18	5.8



Art.	D Ø	E	F	H	Support material	Cup art.	Weight g
00 08 249	8	8.5	5	13.5	brass	01 31 12	1.8



Art.	D Ø	F	H	Support material	Cup art.	Weight g
00 08 250	21	14	23	aluminium	01 32 30	8.6



Art.	A	B	C	H	N	O	P	Q	Support material	Cup art.	Weight g
00 08 256	80	51	2.5	16.6	107	75	102	70	aluminium	01 120 90	244.5



Art.	A	B	C	H	N	O	P	Q	Support material	Cup art.	Weight g
00 08 257	110	35	2.3	16.4	135	60	130	55	aluminium	01 150 75	247.9

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117



SUPPORTS

Art.	A Ø	B Ø	C Ø	D Ø	E	H	Support material	Cup art.	Weight g
00 08 280	35	G1/2"	--	70	12.5	22.5	aluminium	01 150 55	120
00 08 281	65	G1/2"	--	130	12.5	23.5	aluminium	01 210 60	465
00 08 286	35	--	8	70	12.5	22.5	aluminium	01 150 55	125
00 08 287	65	--	8	130	12.5	23.5	aluminium	01 210 60	470

GAS - NPT ADAPTERS

These adapters allow using NPT threaded fittings on vacuum components with gas threads, such as cups, valves and solenoid valves, filtres etc.

FEMALE GAS - MALE NPT ADAPTER

Art.	A Ø	D Ø	E	F	H	T	Adapter material	Weight g
00 08 259	1/8" NPT	G1/8"	10	12	22	14	brass	10
00 08 260	1/4" NPT	G1/4"	12	17	29	19	brass	15
00 08 261	3/8" NPT	G3/8"	16	18	34	22	brass	28
00 08 262	1/2" NPT	G1/2"	17	19	36	27	brass	47
00 08 263	3/4" NPT	G3/4"	19	20	39	32	brass	60
00 08 264	1" NPT	G1"	22	20	42	41	brass	92
00 08 265	1" 1/4 NPT	G1" 1/4	23	23	46	50	brass	132
00 08 266	1" 1/2 NPT	G1" 1/2	23	23	46	60	brass	200
00 08 267	2" NPT	G2"	25	24	49	70	brass	277



MALE GAS - FEMALE NPT ADAPTER

Art.	A Ø	D Ø	E	F	H	T	Adapter material	Weight g
00 08 268	G1/8"	1/8" NPT	10	15	25	14	brass	10
00 08 269	G1/4"	1/4" NPT	11	17	28	19	brass	15
00 08 270	G3/8"	3/8" NPT	12	22	34	22	brass	28
00 08 271	G1/2"	1/2" NPT	14	23	37	27	brass	47
00 08 272	G3/4"	3/4" NPT	14	24	38	32	brass	60
00 08 273	G1"	1" NPT	17	28	45	41	brass	92
00 08 274	G1" 1/4	1" 1/4 NPT	18	28	46	50	brass	132
00 08 275	G1" 1/2	1" 1/2 NPT	19	29	48	60	brass	200
00 08 276	G2"	2" NPT	20	31	51	70	brass	277



THREADED GRUB SCREW WITH CALIBRATED HOLE

These threaded grub screws with calibrated hole are used to reduce the cup suction section, thus reducing vacuum losses in case the cup fails to grip.
They are made with brass and can be inserted in all the cup supports set for this application.



Art.	A Ø	D Ø	F	H	Grub screw material	Weight g
00 08 122	M8	0.9	5	11	brass	2.5
00 08 121	M8	1.2	5	11	brass	2.4
00 08 120	M8	1.5	5	11	brass	2.3



Art.	A Ø	D Ø	F	H	Grub screw material	Weight g
00 08 164	G1/8"	1.2	5	11	brass	3.0
00 08 165	G1/8"	1.5	5	11	brass	3.0
00 08 176	G1/4"	1.2	5	11	brass	4.0

REDUCTION

These standard accessories provide various cup assembly options.
These brass or galvanised steel reductions screwed onto the cup standard support connectors can vary the thread from gas to metric or vice-versa, from male to female or vice-versa, and they can also increase or reduce the size of their threaded diameter.

MF REDUCTION



Art.	D Ø	d Ø	H	Support material	Weight g
00 08 130	G1/4"	M10	14	steel	4.0
00 08 131	G3/8"	M10	14	steel	12.0
00 08 230	G3/8"	G1/4"	14	steel	6.0
00 08 254	1/4" NPT	M10	14	steel	3.9
00 08 255	3/8" NPT	M10	14	steel	11.9
00 08 258	3/8" NPT	G1/4"	14	steel	5.9



MM REDUCTION

Art.	D Ø	E	F	G	H	Reduction material	Weight g
00 08 129	M12	15	14	11	40	brass	4.0



FF REDUCTION FOR GS ARTICULATED JOINT

Art.	D Ø	E	F	G Ø	H	Reduction material	Weight g
00 08 54	M10	13	13.5	M5	36	brass	72
00 08 251	M8	16	15.0	G1/8"	48	brass	102
00 08 252	M12	16	15.0	G1/8"	48	brass	90

Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117

MF REDUCTIONS FOR VRP CUPS

Art.	D	d	F	H	SW	Weight
	Ø	Ø				g
00 08 215	G3/8"	G1/4"	8	14	6	11.5



MF REDUCTIONS FOR VRS - VEP - VES CUPS

Art.	D	d	F	H	SW	Weight
	Ø	Ø				g
00 08 216	G3/8"	G1/4"	8	11.5	6	6.0



MM REDUCTIONS FOR VRP CUPS

Art.	D	d	E	F	SW	Weight
	Ø	Ø				g
00 08 217	G1/4"	G1/4"	15	10	6	16.7
00 08 218	G1/4"	M10 x 1.5	15	12	6	10.2
00 08 219	G1/4"	M14 x 1.5	15	12	6	16.0
00 08 220	G3/8"	G1/4"	14	10	6	18.4
00 08 221	G3/8"	M10 x 1.5	14	12	6	16.3
00 08 222	G3/8"	M14 x 1.5	14	12	6	22.5



MM REDUCTIONS FOR VRS - VEP - VES CUPS

Art.	D	d	E	F	SW	Weight
	Ø	Ø				g
00 08 223	G1/4"	G1/4"	11.5	10	6	13.9
00 08 224	G1/4"	M10 x 1.5	13.0	12	6	10.1
00 08 225	G1/4"	M14 x 1.5	13.0	12	6	15.8
00 08 226	G3/8"	G1/4"	10.5	11	6	16.6
00 08 227	G3/8"	M10 x 1.5	10.5	13	6	14.2
00 08 228	G3/8"	M14 x 1.5	10.5	13	6	20.2



Conversion ratio: inch = $\frac{mm}{25.4}$; pounds = $\frac{g}{453.6} = \frac{Kg}{0.4536}$

GAS - NPT thread adapters available at page 1.117